

IKAR RETRACTING LANYARD | SINGLE

Retracting lanyards are ideal for many fall arrest applications where the anchor point is within 2.5m of your exposed edge or there is a need to reduce fall distances.

This aluminium housed fall arrest block is a sturdy, low maintenance device fitted with internal energy absorption which allows the equipment to last longer even in harsh weather conditions. IKAR Retracting Lanyard series sold by Saferight are Australian Standard AS/NZS1891.3:2020 certified and is UV Degradation tested to 12kN.

It acts as an inertia device, similar to a seat belt, and locks immediately in the event of a fall, reducing both fall distance and forces. The working load limit is up to 136kg person.

KEY FEATURES

- In the event of a free fall, the lanyard locks off immediately reducing fall distances.
- Tested & certified to AS/NZS 1891.3:2020 (BMP No. 718260).
- UV Degradation is tested to 12kN.
- Internal energy absorber designed within the housing, ensuring user protection even when the webbing is fully extended. This also aides in reducing the over all size of the device and reduces exposure of external materials to the environment.

APPLICATIONS

- Working at heights
- Limited free fall
- Perfect for the mining/construction industry



CODE: RLIKAR

HEAD OFFICE: 42 BELMONT AVENUE, BELMONT, WA 6104

PO BOX 176, BELMONT, WA 6984

TEL: +61 08 9334 1011 FAX: +61 08 9334 1001

SALESWA@SAFERIGHT.COM.AU



Quality
ISO 9001
Licence: GEC20205
SAFEGLOBAL



IKAR RETRACTING LANYARD | SINGLE

MATERIALS

- Triple Action Carbon Steel Nickel Plated Karabiner (K1)
- 25mm blue super tape webbing
- Heavy duty aluminium housing
- Weight 1.5kg
- Dimensions - 326 x 105 x 78mm

TRAINING & INSPECTION

- In accordance with AS/NZS 1891.4, all users of height safety equipment must have been trained in its safe use.
- Saferight offers a range of Nationally Recognised Height Safety, Confined Spaces and Rescue Courses.
- Items should always be visually inspected before and after each use as well as undergo inspection by a competent person every 6 months in accordance to AS/NZS 1891.4
- Saferight offers a full inspection service for all Height Safety, Confined Spaces and Rescue equipment.

OPTIONS

- CODE: RLIKAR: 2M webbing length, Triple Action Karabiner (K1)
- CODE: RLIKAR3.5: 3.5M webbing length, Triple Action Karabiner (K1)
- CODE: RLIKARSS: 2M webbing length, triple action stainless steel karabiner (K1S)

TESTING & QUALITY CONTROL

- Certified to AS/NZS 1891.3:2020 (BMP No. 718260)
- Conforms to AS/NZs 1891.1:2007 for UV compliance by an independent NATA test laboratory
- CE marked and certified to EN360
- Saferight is an ISO 9001 Certified Company 6 month servicing requirements in accordance with AS/NZS 1891.4 100% visually inspected Safety factor of 2: Load bearing web of the fly end of the webbing is UV tested to ensure a guaranteed strength of 12 kN is maintained at the end of the 10 year life of the product (eg 2 x 6 Kn = 12 kN SWL for a 136kg user)



HEAD OFFICE: 42 BELMONT AVENUE, BELMONT, WA 6104

PO BOX 176, BELMONT, WA 6984

TEL: +61 08 9334 1011 FAX: +61 08 9334 1001

SALESWA@SAFERIGHT.COM.AU