

H10 HARNESS

H10 BASIC WORKING AT HEIGHTS HARNESS DATASHEET



PRODUCT FEATURES AND INFORMATION

The H10 Basic Working at Heights Full Body Harness is a light weight and comfortable design and comes with Front and Rear D Attachments and 2 Bar 3 Bar Buckles.

DATASHEET



H10 HARNESS

PRODUCT FEATURES AND INFORMATION



Main Features

- Light weight, comfortable design
- Front Fall Arrest D Ring
- Front and rear attachment points
- Rear Dorsal D
- 2-Bar & 3-Bar Buckles

Accessories & Add-ons

The H10 is available with optional extras including:

- Side D's (H10D)

For more specialised applications Saferight offer a fully customisable H11 Harness or the H12 Deluxe Harness

All harnesses to be inspected every 6 months (minimum) as required by AS/NZS 1891.4 : 2009

Materials & Construction

- 44mm Polyester webbing
- Minimum breaking load 15 kN
- Zinc plated fittings as standard
- Water/UV resistant webbing
- Weight 1.2kg

Testing & Quality Control

- 100% visual inspection
- Conforms to AS/NZS1891.1:2007
- Manufactured under an ISO 9001 CERTIFIED QUALITY ASSURANCE SYSTEM

Safe Working Load (SWL)

- Maximum operator weight including tools shall be no more than 140kg